

Full Body Camera

FEATURES

- Indoor Operation
- Sony 1/3" **Super** HAD CCD
- Sony DSP (Digital Signal Processor)
- Horizontal Resolution of **540TVL**
- Automatic White Balance (AWB)
- C/CS Mount Lens Adaptable without Additional Adaptor
- Material : Aluminum
- DC12V/AC24V Dual Power (Non-polarity)
- CE, FCC, RoHS Compliance



GSP-FB54S

SPECIFICATIONS

Model	GSP-FB54S
Image Sensor	Sony 1/3" Super HAD CCD
TV System	NTSC or PAL
Effective Pixels	410K(NTSC)/470K(PAL)
Horizontal Resolution	540TVL
White Balance	Automatic White Balance(AWB)
Scanning System	525 Lines(NTSC), 625 Lines(PAL) 2 : 1 Interlace
Sync. System	Internal(DC12V)/L.L(External/AC24V) : Auto Switching
Scanning Frequency	(H)15.734KHz (V)59.94Hz [NTSC], (H)15.625KHz (V)50Hz [PAL]
Min. Illumination	0.5 Lux
Lens	C/CS Mountable (Not Included)
Electrical Shutter	1/60 ~ 100,000(NTSC), 1/50 ~ 100,000(PAL)
S/N Ratio	More than 48dB (AGC Off)
Gamma Correction	0.45
Video Output	VBS 1.0Vp-p Composite
Function Key	AGC/A.I, E.E/BLC/FLK/PUSH, ATW S/W, DC Level Adjustment
Electrical	
Power Source	DC12V/AC24V Dual Power (Non-Polarity)
Power Consumption	DC12V : 300mA / AC24V : 5W
Connector Video Output	BNC
Power Output	Terminal Block
Environmental	
Operating Temperature	14°F ~ 122°F (-10°C ~ 50°C)
Storage Temperature	-22°F ~ 140°F (-30°C ~ 60°C)
Operating Humidity	Up to 90%RH
Mechanical	
Camera Mount	1/4"-20UNC thread on top and bottom
Material	Aluminum
Color	Ivory
Dimensions(mm)	65(W)X54(H)X133(D)
Weight	300g